

# A Topical Crawler for Uncovering Hidden Communities of Extremist Micro-Bloggers on Tumblr

Swati Agarwal, Ashish Sureka

IIIT-Delhi | Indraprastha Institute of Information Technology

*swatia@iiitd.ac.in, ashish@iiitd.ac.in*

May 18, 2015

# Table of Contents

- 1 Research Motivation and Aim
  - Research Motivation
  - Research Aim
- 2 Solution Approach
  - Classifier Training
  - High-Level Framework and Architecture
- 3 Experimental Results and Conclusions
  - Confusion Matrix and Accuracy Results
- 4 References

# Table of Contents

- 1 Research Motivation and Aim
  - Research Motivation
  - Research Aim
- 2 Solution Approach
  - Classifier Training
  - High-Level Framework and Architecture
- 3 Experimental Results and Conclusions
  - Confusion Matrix and Accuracy Results
- 4 References

## Research Motivation and Aim

- ▶ Tumblr is a popular and widely-used micro-blogging website
- ▶ Previous research shows that such websites are used as a platform for disseminating hate and extremism (due to low barrier to publication and anonymity) [1][2][3][4][5]
- ▶ Automatic identification of hate and extremism promoting posts and bloggers is an important (from the perspective of the website moderators and law enforcement agencies) and a technically challenging problem
- ▶ Large volume of data on Tumblr, free-form text and noisy content makes automated analysis technically challenging [1][2][3][4][5]

# A Concrete Example of Different Types (Text, Video, Audio) of Hate Promoting Post on Tumblr

fagflow

Why are you libs so afraid to call out muslim extremists? There are 1.6 billion muslims in the world and roughly 200 million of them are radical jihadists and they are to blame for the terrorist attacks recently. their main goal is to inforce sharia law on all non-muslims and kill all who disagree because the quran says to kill all non believers. But you run to their defense and play devils advocate. like. why...

#liberals #isis #al queda #holy quran

1,130 notes

fnhfal

Islamic Jihad

#Islamic Jihad #jihad #Israel #Islam #M

58 notes

godisnot

Religion of peace?

#Islam #Religion of Peace #Jihad #Nazi

boko haram, islam, muslim, radical islam, terrorist, jihad, isis, liberals, al queda, holy quran, je suis charlie, Islamic Jihad, Israel, ak47, guns, rifle, hate, anti-American, violence, battle, weapon, religion of peace

## Tags/Keywords associated with the post

## Research Motivation and Aim

- ▶ To investigate the application of a topical crawling based algorithm for retrieving hate promoting bloggers on Tumblr
- ▶ To examine the effectiveness of a random-walk based approach in social network graph traversal
- ▶ to examine the effectiveness of *re-blogging* and *like* on a post as the links between two bloggers and conduct experiments on large real world dataset to demonstrate the effectiveness of our approach

## Research Motivation and Aim

- ▶ To investigate the application of a topical crawling based algorithm for retrieving hate promoting bloggers on Tumblr
- ▶ To examine the effectiveness of a random-walk based approach in social network graph traversal
- ▶ to examine the effectiveness of *re-blogging* and *like* on a post as the links between two bloggers and conduct experiments on large real world dataset to demonstrate the effectiveness of our approach


## Research Motivation and Aim

- ▶ To investigate the application of a topical crawling based algorithm for retrieving hate promoting bloggers on Tumblr
- ▶ To examine the effectiveness of a random-walk based approach in social network graph traversal
- ▶ to examine the effectiveness of *re-blogging* and *like* on a post as the links between two bloggers and conduct experiments on large real world dataset to demonstrate the effectiveness of our approach


# Table of Contents

- 1 Research Motivation and Aim
  - Research Motivation
  - Research Aim
- 2 **Solution Approach**
  - Classifier Training
  - **High-Level Framework and Architecture**
- 3 Experimental Results and Conclusions
  - Confusion Matrix and Accuracy Results
- 4 References

# Flow Sequence of Exemplary Data Collection Process



# Multi-Phase - Processing Pipeline



## Key Steps in the Proposed Solution

- ▶ Proposed solution framework is an iterative multi-step process primarily consisting of five phases: features (posts) extraction, data pre-processing, classification, frontier extraction and graph traversal
- ▶ We build a statistical model from the exemplary documents collected separately by semi-automatic process. To compute the relevance of each blogger, we use character level n-gram language modeling approach.
- ▶ We perform a graph traversal which results in a connected graph, where nodes represents a blogger (hate promoting) and edges represent the links (re-blog and like) between two bloggers. We perform social network analysis on the resultant graph and locate extreme right communities of hate promoting bloggers.

## Key Steps in the Proposed Solution

- ▶ Proposed solution framework is an iterative multi-step process primarily consisting of five phases: features (posts) extraction, data pre-processing, classification, frontier extraction and graph traversal
- ▶ We build a statistical model from the exemplary documents collected separately by semi-automatic process. To compute the relevance of each blogger, we use character level n-gram language modeling approach.
- ▶ We perform a graph traversal which results in a connected graph, where nodes represents a blogger (hate promoting) and edges represent the links (re-blog and like) between two bloggers. We perform social network analysis on the resultant graph and locate extreme right communities of hate promoting bloggers.

## Key Steps in the Proposed Solution

- ▶ Proposed solution framework is an iterative multi-step process primarily consisting of five phases: features (posts) extraction, data pre-processing, classification, frontier extraction and graph traversal
- ▶ We build a statistical model from the exemplary documents collected separately by semi-automatic process. To compute the relevance of each blogger, we use character level n-gram language modeling approach.
- ▶ We perform a graph traversal which results in a connected graph, where nodes represents a blogger (hate promoting) and edges represent the links (re-blog and like) between two bloggers. We perform social network analysis on the resultant graph and locate extreme right communities of hate promoting bloggers.

# Table of Contents

- 1 Research Motivation and Aim
  - Research Motivation
  - Research Aim
- 2 Solution Approach
  - Classifier Training
  - High-Level Framework and Architecture
- 3 Experimental Results and Conclusions
  - Confusion Matrix and Accuracy Results
- 4 References

## Confusion Matrix and Accuracy Results


**Table:** Confusion Matrix for One Class Classifier

|        |          | Predicted |         |
|--------|----------|-----------|---------|
|        |          | Positive  | Unknown |
| Actual | Positive | 290       | 45      |
|        | Unknown  | 92        | 173     |

**Table:** Accuracy Results for One Class Classifier

| Precision | Recall | F-Score | Accuracy |
|-----------|--------|---------|----------|
| 0.75      | 0.86   | 0.80    | 0.77     |

# Social Network Analysis



**Figure:** Cluster Representation of Social Network Graphs- 'Posts Liked by' (left) and 'Posts Re-blogged By' (right)

## Conclusions

- ▶ We execute our topical crawler for a given seed blogger and traverse through Tumblr network using random walk algorithm
- ▶ Results shows that the precision, recall and f-score are reasonably high and we are able to predict hate promoting bloggers with an accuracy of 77%
- ▶ Our experimental analysis reveals that re-blogging is a good indicator of connection between two bloggers
- ▶ We locate users who are central and influential among all and play major role in the discovered communities

## Conclusions

- ▶ We execute our topical crawler for a given seed blogger and traverse through Tumblr network using random walk algorithm
- ▶ Results shows that the precision, recall and f-score are reasonably high and we are able to predict hate promoting bloggers with an accuracy of 77%
- ▶ Our experimental analysis reveals that re-blogging is a good indicator of connection between two bloggers
- ▶ We locate users who are central and influential among all and play major role in the discovered communities

## Conclusions

- ▶ We execute our topical crawler for a given seed blogger and traverse through Tumblr network using random walk algorithm
- ▶ Results shows that the precision, recall and f-score are reasonably high and we are able to predict hate promoting bloggers with an accuracy of 77%
- ▶ Our experimental analysis reveals that re-blogging is a good indicator of connection between two bloggers
- ▶ We locate users who are central and influential among all and play major role in the discovered communities

## Conclusions

- ▶ We execute our topical crawler for a given seed blogger and traverse through Tumblr network using random walk algorithm
- ▶ Results shows that the precision, recall and f-score are reasonably high and we are able to predict hate promoting bloggers with an accuracy of 77%
- ▶ Our experimental analysis reveals that re-blogging is a good indicator of connection between two bloggers
- ▶ We locate users who are central and influential among all and play major role in the discovered communities

# Table of Contents

- 1 Research Motivation and Aim
  - Research Motivation
  - Research Aim
- 2 Solution Approach
  - Classifier Training
  - High-Level Framework and Architecture
- 3 Experimental Results and Conclusions
  - Confusion Matrix and Accuracy Results
- 4 References

# References I



Swati Agarwal and Ashish Sureka.

Using knn and svm based one-class classifier for detecting online radicalization on twitter.

In *Distributed Computing and Internet Technology (ICDCIT)*, pages 431–442, 2015.



Elizabeth Amparo Cano Basave, Yulan He, Kang Liu, and Jun” Zhao.

A weakly supervised bayesian model for violence detection in social media.

In *Sixth International Joint Conference on Natural Language Processing*, pages 109–117, 2013.



Shamanth Kumar, Fred Morstatter, Reza Zafarani, and Huan Liu.

Whom should i follow?: Identifying relevant users during crises.

In *ACM Conference on Hypertext and Social Media (HT)*, pages 139–147, 2013.



Ashish Sureka and Swati Agarwal.

Learning to classify hate and extremism promoting tweets.

In *Joint Conference in Intelligence Security Informatics (JISIC)*, pages 320–320. IEEE, 2014.

## References II



Jiejun Xu, Tsai-Ching Lu, Ryan Compton, and David Allen.

Civil unrest prediction: A tumblr-based exploration.

In *Social Computing, Behavioral-Cultural Modeling and Prediction*, pages 403–411. Springer, 2014.

# Thank you!

Contact:

[swatia@iiitd.ac.in](mailto:swatia@iiitd.ac.in)

[ashish@iiitd.ac.in](mailto:ashish@iiitd.ac.in)